

Citizen CMP-20II & CMP-30II



Citizen CMP-20II & CMP-30II – Compact and enduring

- ✓ Powerful battery for the whole working day
- ✓ High print speed on media up to 2 or 3 inches wide
- ✓ Drop-in paper loading mechanism for quick media changes
- ✓ Optional equipment with Wi-Fi or Bluetooth
- ✓ Compatible with all current operating systems

Features

Printing technology: Thermodirect

Printing width (max.): 48 / 72 mm

Resolution: 203 dpi

Printing speed (max.): 80 / 100 mm/sec.

Media width: 25 to 58 / 80 mm

Media sensor: Paper end, opt.: Blackmark, transparency sensor

Operating systems: Android, iOS, Windows, Linux, macOS

Printer languages: Emulation CPCL and ESC/POS, optional ZPL upgrade

Connection: USB, RS-232/serial, opt.: WLAN, Bluetooth

Protection class: IP42, drop height 1.5 m

Dimensions (W x L x H): 96 x 136 x 58 mm / 120 x 152 x 70 mm

Weight: 442 / 630 g

Optional accessories

Bags and shoulder straps

Car adapter

Additional battery

External battery charger

Citizen CMP-20II & CMP-30II

Resolution	203 dpi
Print Speed (maximum)	3 inches (80 mm/s)
Print Width (maximum)	48 mm
Media Width (min to max)	58 mm
Roll Size (max), Core Size	Diameter 1.88 inches (48 mm)
Media Sensor	Paper end
Main Interface	Dual Interface Serial (RS-232 /mini DIN connector), USB (mini B connector)
Interface	Bluetooth Class 2 , Bluetooth with Apple™ MFi compatibility, Compact Wireless LAN
Environmental rating, drop test	Exceeds IP42. Survives multiple drops of 1.5 metres
Battery type and capacity	Li-Ion, 7.4 volt, 1800 mAh
Emulations (Languages)	ESC/POS™ , CPCL™ compatibility, Zebra® ZPL-II®
Size (W x D x H) and Weight	96 x 136 x 58 mm, 0.42 Kg

Citizen CMP-20II & CMP-30II

Auflösung	203 dpi
Druckgeschwindigkeit (Max.)	4 Zoll pro Sekunde (100 mm/Sek.)
Druckbreite (Maximal)	72 mm
Medienbreite (min. - max.)	25 bis 80 mm
Rollengröße (max.), Kerngröße	Durchmesser 2.20 Zoll (56 mm)
Mediensensor	Papierende und Blackmark
Hauptschnittstelle	Dual Interface Seriell (RS-232 / Mini-DIN-Stecker), USB (Ministecker Typ B)
Schnittstelle	Bluetooth mit Apple™ MFi Kompatibilität, Bluetooth Klasse 2, Compact Wireless LAN
Schutzart, Falltest	Übertrifft IP42, übersteht mehrfaches Herunterfallen aus 1,5 m
Batterietyp und Kapazität	Hard pack 7,4V 2600mAh
Emulationen (Sprachen)	CPCL™ Kompatibilität, ESC/POS™ , Zebra® ZPL-II®
Abmessungen (B x T x H) und Gewicht	120 x 152 x 70 mm, 0,6 kg