

Nicht mehr verfügbar! Wir empfehlen: Datalogic Rhino II



## Robust and flexible

- ✓ Industrial grade design for use in demanding environments
- ✓ Resistant construction with Corning Gorilla Glass and IP65 sealing against damage, dust and jet water
- ✓ Flexible accessories and ergonomic design for versatile uses
- ✓ Optional docking station for use as a powerful stacker terminal
- ✓ Stable data connection with current Bluetooth and Wi-Fi technologies

## Features

**Display:** 7 inch, 1024 x 600 px / 10 inch, 1280 x 800 px

**Operating system:** Windows 10

**CPU:** Intel 1.46 GHz Dual-Core

**Memory:** 4 GB RAM, 32 / 64 / 128 GB

**Battery:** 2500 mAh, handle 2600 mAh

**Network connections:** WLAN, Bluetooth, USB

**Additional features:** camera, barcode scanner

**Protection:** IP65, drop-proof up to 1.2 m

**Operating temperature:** -20 - 50 °C

**Dimensions (W x L x H):** 150 x 187 x 38 / 279 x 187 x 38 mm

**Weight:** 733 / 1044 g

## Optional accessories

**Docking stations**

**Mounts**

**3-way battery charging station**

**Hand strap**

**2D Barcode Scanner (Standard or Auto Range)**

**Hot Swap Battery**

**Bags**

## WIRELESS COMMUNICATIONS

<b>Personal Area Network (WPAN)</b>	Bluetooth Wireless Technology 4.0
<b>Local Area Network (WLAN)</b>	Wi-Fi 802.11 a/b/g/n/ac/r (2.4 GHz and 5 GHz)
<b>Antennas</b>	Diversity antennas embedded

## ELECTRICAL

<b>Battery</b>	Internal Battery 2,500 mAh @ 7.2 VDC; 18 W Handgrip Battery 2,600 mAh @ 7.4 VDC; 19.4 W Battery Operating: -20 to 50 °C / -4 to 122 °F
<b>Docking Station Power Supply</b>	12-48 VDC or 110/230 VAC
<b>Light Indicators</b>	On front bezel: charge, internal battery status, external (handgrip) battery status, temperature protection status

## ENVIRONMENTAL

<b>Drop Resistance</b>	Withstands repeated drops from 1.2 m / 4.0 ft onto concrete and hundreds of tumbles as per standard IEC 68068-2-32 (method 2)
<b>Humidity</b>	10 to 90% at 40 °C / 104 °F; non-condensing
<b>Temperature</b>	Operating: -20 to 50 °C / -4 to 122 °F Storage: -40 to 60 °C / -40 to 140 °F
<b>Particulate and Water Sealing</b>	IP65
<b>Shock and Vibration</b>	Tested accordingly to EN 60068-2-64:2008 with forklift vehicle severity level, also meets class 5M3 of EN 60721-3-5: 1998 (landcrafts)
<b>Durability</b>	Designed to meet MIL-STD-810G

## INTERFACES

<b>Interfaces on Device</b>	USB: 1 x USB-C 2.0
<b>Interfaces on Dock Station</b>	RJ45: Ethernet 10/100 Mbps.; USB: 2 x USB 2.0; RS-232, Audio Jack (optional) CAN bus interface available (optional with a CAN2USB connector)

## SAFETY & REGULATORY

<b>Agency Approvals</b>	The product meets necessary safety and regulatory approvals for its intended use.
<b>Certifications</b>	Certified for CE/FCC

## PHYSICAL CHARACTERISTICS

<b>Camera</b>	5 MP rear camera
<b>Construction</b>	Automotive grade ASA blended with Polycarbonate for extreme conditions; Rubber overmold for added protection on drops
<b>Dimensions</b>	7 inch: 15.0 x 18.7 x 3.8 cm / 5.9 x 7.3 x 1.5 in 10 inch: 27.9 x 18.7 x 3.8 cm / 10.9 x 7.3 x 1.5 in
<b>Display</b>	7 inch: WSVGA 1024 x 600, 420 cd/m <sup>2</sup> 10 inch: WXGA 1280 x 800, 350 cd/m <sup>2</sup>
<b>Function Buttons</b>	Front keys: SW keyboard pop-up; On screen setup menu; Customizable function button
<b>Hand Grip</b>	Mobile handgrip with optional hot swappable battery and Standard or Auto Range 2D imager; Hardened glass scan window; Standard range up to 1.1 m / 43 inches; Extra-long range up to 15 m / 50 ft
<b>Mounting</b>	Docks for stationary or vehicle use (VESA 75 mm pattern)
<b>Speakers</b>	Built in speaker or optional audio output for external speaker
<b>Touchscreen</b>	Multi-Touch, projected capacitive touch with Corning Gorilla Glass with 1.6 mm thickness
<b>Voice Support</b>	Wireless via Bluetooth v4
<b>Weight (with Battery)</b>	7 inch: 733 g / 25.8 oz 10 inch: 1044 g / 36.8 oz

## SOFTWARE

<b>Device Management</b>	SOTI, Ivanti/Wavelink available (not pre-licensed)
<b>Terminal Emulation</b>	Ivanti/Wavelink, StayLinked available (not pre-licensed)

## SYSTEM

<b>Audio</b>	Intel® High Definition Audio (Intel® HD Audio)
<b>Operating System</b>	Windows® 10 IoT Enterprise 64-bit
<b>Processor</b>	Intel 1.46 GHz Dual-Core
<b>Memory</b>	RAM: 4 GB
<b>Storage</b>	CFast: 32GB (optional 64/128 GB)

## WARRANTY

<b>Warranty</b>	1-Year Factory Warranty
-----------------	-------------------------