

Nicht mehr verfügbar!



## Datalogic Memor K – Kompakter Einstieg

- ✓ Geringes Gewicht und kompakte Abmessungen für einfache Handhabung
- ✓ SoftSpot-Trigger und Greenspot-Technologie für einfache und schnelle Datenerfassung
- ✓ Hintergrundbeleuchtete Tastatur und 4 Zoll großes Display
- ✓ Flüssiges Arbeiten durch Android, starken Prozessor und großen Arbeitsspeicher
- ✓ Zuverlässige Datenanbindung mit modernem WLAN, Bluetooth und NFC

## Eigenschaften

**Display:** 4 Zoll, Dragontrail Glass

**Tastatur:** 24 Tasten (hintergrundbeleuchtet), seitlich 2 Scan- und 2 freie Tasten

**Betriebssystem:** Android 9

**Lesbare Codes:** 1D und 2D

**Akku:** 3800 mAh, 12 h Laufzeit, wechselbar

**Drahtlose Schnittstellen:** WLAN, Bluetooth, NFC

**Zusätzliche Features:** 8 MP Kamera, 3-Achsen Sensor

**Schutz:** IP54, bis 1,2 m sturzsicher

**Betriebstemperatur:** -20 – 50 °C

**Abmessungen (B x L x H):** 71 x 160 x 17 mm

**Gewicht:** 268 g

## Optionales Zubehör

**Dockingstation**

**Hüfttasche**

**Schutzhülle**

## WIRELESS COMMUNICATIONS

<b>Local Area Network (WLAN)</b>	IEEE 802.11 a/b/g/n/ac/d/e/i/w; Frequency range: Country dependent, typically 2.4 GHz and 5 GHz bands
<b>Personal Area Network (WPAN)</b>	Bluetooth wireless technology v5 (Classic Bluetooth wireless technology and BLE)
<b>NFC Communication</b>	Support for the following standards: ISO14443-4 (type-A, type-B); ISO15693; Mifare; Felica

## DECODING CAPABILITY

<b>1D / Linear Codes</b>	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.
<b>2D Codes</b>	Aztec Code, Data Matrix, HanXin Code, MaxiCode, MicroQR Code, QR Code, EAN/JAN Composites, UPC A/E Composites
<b>Postal Codes</b>	Australian Post, Japan Post, British Post; China Post; IMB, Korea Post, KIX Code, PLANET, POSTNET, Royal Mail Code (RM4SCC)
<b>Stacked Codes</b>	Micro-PDF417, MacroPDF, PDF417, GS1 DataBar Composites, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional

## ELECTRICAL

<b>Battery</b>	Removable battery pack 3800 mAh with rechargeable Li-Ion batteries
----------------	--

## ENVIRONMENTAL

<b>Drop Resistance</b>	Withstands 18 drops from 1.2 m / 4 ft to concrete according to IEC62-2-32 Method 1. Device with rubber boot: withstands 18 drops from 1.5 m / 5 ft to concrete according to IEC62-2-32 Method 1 with rubber boot.
<b>Tumbles</b>	Device: exceeds 400 hits at 0.5 m (200 cycle) per IEC 60068-2-32 specification. Device with rubber boot: exceeds 600 hits at 0.5 m (300 cycle) per IEC 60068-2-32 specification.
<b>Particulate and Water Sealing</b>	IP54
<b>Temperature</b>	Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F

## INTERFACES

<b>Interfaces</b>	USB-C: High Speed USB 2.0 OTG
-------------------	-------------------------------

## SENSORS

<b>Accelerometer</b>	3-Axis accelerometer to detect orientation
<b>Ambient Light</b>	Auto adjusts display backlight
<b>Proximity</b>	Auto deactivates display when close to face

## PHYSICAL CHARACTERISTICS

<b>Dimensions</b>	16.0 x 7.1 x 1.7 cm / 6.2 x 2.7 x 0.66 in
<b>Display</b>	4 inch WVGA resolution 800 x 480; LED backlight; Touch Screen: 5 points multi-touch capacitive panel with Dragontrail hardened glass
<b>Keys</b>	Backlighted 24 keys rubber keyboard, plus two side scan keys and two programmable side keys
<b>Weight</b>	With Battery: 268 g / 9.4 oz

## READING PERFORMANCE

<b>Camera</b>	Resolution: 8 MP; Illumination: LED flash; Lens: Auto focus
<b>Scan Engine</b>	2D Ultra slim area imager (supports 1D / 2D codes); Datalogic's 'Green Spot' for good-read feedback; Resolution: VGA (640 x 480 pixels)
<b>Minimum Element Width</b>	1D Linear: 0.101 mm / 4 mils; PDF417: 0.167 mm / 6.6 mils; Data Matrix: 0.190 mm / 7.5 mils

## SAFETY & REGULATORY

<b>Agency Approvals</b>	The product meets necessary safety and regulatory approvals for its intended use.
<b>Environmental Compliance</b>	Complies to EU RoHS

## SOFTWARE

<b>Applications</b>	Datalogic's SoftSpot technology for configurable soft triggers
<b>Provisioning</b>	QR Code enrollment
<b>Configuration and Maintenance</b>	Scan2Deploy Studio, DXU
<b>Development</b>	Java, Cordova and Xamarin SDK available
<b>MDM</b>	SOTI MobiControl, VMware AirWatch, Ivanti Avalanche, 42Gears SureMDM

## SYSTEM

<b>Expansion Slots</b>	Micro-SD card slot: Compatible with Micro SD-HC cards, up to 64 GB; User-accessible
<b>Memory</b>	System RAM: 3 GB; eMMC Flash: 32 GB
<b>Microprocessor</b>	2 GHz Octa-core
<b>Operating System</b>	Android 9
<b>Real-Time Clock</b>	Time and date stamping under software control

## WARRANTY

<b>Warranty</b>	1-Year Factory Warranty
-----------------	-------------------------